



MODEL	PRIMARY A & B	W	L	H	SECONDARY		E	F	WEIGHT kg		MINIMUM SEC. VOLUME LITRES
					C	D			HS	HD	
H 025-**-32	HS - DN32 PN6 HD - DN40 PN6	420	640	1250	35	35	0	0	120	130	45
H 050-**-32	HS - DN32 PN6 HD - DN40 PN6	420	640	1250	35	35	0	0	125	135	75
H 075-40-32	DN40 PN6	420	640	1250	35	42	0	0	135	140	90
H 100-40-32	DN40 PN6	450	800	1250	35	42	0	10	170	180	125
H 150-40-32	DN40 PN6	450	800	1250	35	42	30	10	180	190	150
H 200-50-50	DN50 PN6	450	1000	1530	54	54	60	70	280	305	200
H 250-50-50	DN50 PN6	450	1000	1530	54	54	60	70	290	315	250
H 300-50-50	DN40 PN6	450	1000	1530	54	54	60	70	300	325	300
H 350-50-50	DN50 PN6	450	1000	1750	54	54	60	120	310	335	350
H 400-65-65	DN65 PN6	540	1000	1750	DN65 PN10	DN65 PN10	100	135	540	565	400
H 450-65-65	DN65 PN6	540	1000	1750	DN65 PN10	DN65 PN10	100	135	550	575	450
H 500-65-65	DN65 PN6	540	1000		DN65 PN10	DN65 PN10	100	135	550	575	500

HS DESIGNATES SINGLE DUTY PUMP SYSTEM  
HD DESIGNATES TWIN DUTY/STANDBY PUMP SYSTEM (AS SHOWN)